

Ocean Containers



General Purpose Containers

Suitable for any general cargo

| | Maximum Inside Dimensions | | | Door Opening | | Top Opening | | Tare Weight (kg/lbs) | Cubic Capacity (m ³ /cu.ft.) | Maximum Payload (kg/lbs) |
|----------------------------------|---------------------------|--------------------|---------------------|--------------------|--------------------|-------------|---|-------------------------|--|-----------------------------|
| | L | W | H | W | H | L | W | | | |
| 20' Dry Freight Container | 5,895m 19'4 1/8" | 2,350m 7'8 1/2" | 2,392m 7'10 1/8" | 2,340m 7'8 1/8" | 2,292m 7'6 1/4" | | | 2,250 kg 4,960 lbs | 33,2 m ³ 1,172 cu.ft. | 28,230 kg 62,240 lbs |
| 40' Dry Freight Container | 12,029m 39'5 1/2" | 2,350m 7'8 1/2" | 2,392m 7'10 1/8" | 2,234m 7'8 1/2" | 2,292m 7'6 1/4" | | | 3,780 kg 8,330 lbs | 67,7 m ³ 2,390 cu.ft. | 26,700 kg 58,870 lbs |



High Cube General Purpose Containers

Specifically for light, voluminous cargoes or those for excessive height (up to 2,67m)

| | Maximum Inside Dimensions | | | Door Opening | | Top Opening | | Tare Weight (kg/lbs) | Cubic Capacity (m ³ /cu.ft.) | Maximum Payload (kg/lbs) |
|--------------------------------|---------------------------|--------------------|---------------------|--------------------|---------------------|-------------|---|-------------------------|--|-----------------------------|
| | L | W | H | W | H | L | W | | | |
| 40' High Cube Container | 12,024m 39'5 3/8" | 2,350m 7'8 1/2" | 2,697m 8'10 1/8" | 2,340m 7'8 1/8" | 2,597m 8'6 1/4" | | | 4,020 kg 8,860 lbs | 76,3 m ³ 2,694 cu.ft. | 26,460 kg 58,340 lbs |
| 45' High Cube Container | 13,582m 44'6 1/2" | 2,347m 7'8 1/4" | 2,690m 8' 10" | 2,340m 7' 8" | 2,584m 8' 5 3/4" | | | 4,110 kg 9,061 lbs | 85,7 m ³ 3,026 cu.ft. | 28,390 kg 62,589 lbs |



Open Top Containers

Especially for overheight cargo, loading from top side; eg. - by crane, loading from door side: eg. - with cargo hanging from overhead tackle.


| | Maximum Inside Dimensions | | | | Top Opening | | Tare Weight (kg/lbs) | Cubic Capacity (m ³ /cu.ft.) | Maximum Payload (kg/lbs) |
|-------------------------------|---------------------------|--------------------|---------------------|--------------------|-----------------------|-------------------|-------------------------|--|-----------------------------|
| | L | W | Middle | Side | L | W | | | |
| 20' Open Top Container | 5,895m 19' 4" | 2,350m 7'8 1/2" | 2,394m 7'10 1/4" | 2,364m 7' 9" | 5,895 m 19'4" | 2,350 m 8 1/2" | 2,100 kg 4,630 lbs | 32,45 m ³ 1,146 cu.ft. | 21,900 kg 48,280 lbs |
| 40' Top Open Container | 12,023m 39'5 3/8" | 2,335m 7' 8" | 2,378m 7'9 5/8" | 2,318m 7'7 1/4" | 12,023 m 39'5 3/8" | 2,335 m 7'8" | 3,800 kg 8,380 lbs | 66,7 m ³ 2,354 cu.ft. | 26,680 kg 58,820 lbs |



Flats

Specifically for heavy-lifts and overwidth cargoes. Strong bottom construction with fixed endwalls (which allow bracing and lashing of cargo as well as stacking).

| | Maximum Inside Dimensions | | | Door Opening | | Top Opening | | Tare Weight (kg/lbs) | Cubic Capacity (m ³ /cu.ft.) | Maximum Payload (kg/lbs) |
|----------------------------------|---------------------------|--------------------|--------------------|--------------|---|-------------|---|-------------------------|--|-----------------------------|
| | L | W | H | W | H | L | W | | | |
| 20' Flat Rack Container | 5,625m 18'5 3/8" | 2,208m 7'2 7/8" | 2,172m 7'1 1/2" | | | | | 2,800 kg 6,170 lbs | | 21,200 kg 46,740 lbs |
| 40' Flat Rack Container | 11,712m 38'5 1/8" | 2,232m 7'3 7/8" | 1,981m 6'6" | | | | | 4,750 kg 10,470 lbs | | 25,730 kg 56,730 lbs |
| 40' Collapsible Flat Rack | 11,660m 38'3 1/8" | 2,200m 7'2 5/8" | 2,245m 7'4 3/8" | | | | | 5,700 kg 12,570 lbs | | 39,300 kg 86,640 lbs |



Platforms

Especially for heavy loads and oversized cargo

| | Maximum Inside Dimensions | | | Door Opening | | Top Opening | | Tare Weight (kg/lbs) | Cubic Capacity (m ³ /cu.ft.) | Maximum Payload (kg/lbs) |
|--|---------------------------|--------------|---|--------------|---|-------------|---|-------------------------|--|-----------------------------|
| | L | W | H | W | H | L | W | | | |
| 20' Steel Frame with Softwood Floor | 6,058m 20' | 2,438m 8' | | | | | | 2,100 kg 4,630 lbs | | 21,900 kg 48,280 lbs |
| 40' Steel Frame with Softwood Floor | 12,192m 40' | 2,438m 8' | | | | | | 4,200 kg 9,260 lbs | | 40,800 kg 89,950 lbs |